

SUBMITTAL SHEET

JOB NAME	ITEM TAG
JOB LOCATION	PART NUMBER
CONTRACTOR	DATE
ENGINEER APPROVAL	DATE

LEAD-FREE FLARE X FNPT ADAPTER

T-4105NL

Designed and manufactured for underground water service installations only.

Available in copper tube sizes 3/4" through 2" Flare x FNPT.

Specifications:

Manufactured in compliance with the latest version of AWWA C800, for high pressure.

MA	FERIAL SPECIFICATION		
	PART	MATERIAL	
1	Body	Lead-Free Cast Bronze	
2	Flare Nut	Cast Bronze	

DIMENSIONS - Inch				
Size	Α	В	Item No.	
3/4"	2.48	1.53	313-024NL	
1″	2.98	1.84	313-025NL	
1-1/4″	3.55	2.37	313-026NL	
1-1/2″	3.94	2.91	313-027NL	
2″	5.01	3.54	313-028NL	

Certifications/Listings:

Third-party certified.


ANSI/NSF 61: Drinking water system components health effects. ANSI/NSF 372: Drinking water system components-lead content.

Standards:

AWWA C800: Underground service line valves and fittings. ANSI/ASME B1.20.1: Pipe threads, general purpose, Inch.







Pictured: T-4105NL Cut-away